ALLNET Zubehör für Entwicklungsplatinen 4duino Board Sensor Extended Edition V4

Artikelnummer	996865298
Gewicht	1kg
Länge	1mm
Breite	1mm
Höhe	1mm

Produktbeschreibung

ALLNET Zubehör für Entwicklungsplatinen 4duino Board Sensor Extended Edition V4

Produktbeschreibung:

4duino sensor extended edition V4DescriptionEach
functional module has buckled port with VCC,
GND and Output, which has corresponding port on
the Sensor Shield,
connected with a plain 2.54mm dual-female cable
you may start playing already.
Buckled brick cables are like cement for bricks,
make the connections easier, secure and more professional looking.
 ,Sensor Shield V4.0 ,allows you to connect
to various modules like sensors,
servos, relays, buttons, potentiometers.just plug &amp,
play! Each functional module has buckled port with VCC,
GND and Output, which has corresponding port on
the Sensor Shield,
connected with a plain 2.54mm dual-female cable
you may start playing already.
Buckled brick cables are like cement for bricks,
make the connections easier, secure and more professional looking.
Operating Voltage: 5VDC
Input Voltage (recommended): 7-12VDC
Input Voltage (limits): , 6-20VDC
Buckled Analog Port:Handy, solid connection to
6 Analog inputs with VCC/GND
Digital IO port:13 ports prepared to digital modules or servos
Analog IO Port:2.54 grid male pin header connections
Buckled Communication Port:Selectable between I2C and UART
Compatible with: ,Arduino Duemilanove UNO
Mega2560 ATMEL ,Specification: just plug &amp,
play Operating Voltage: 5VDC Input Voltage (recommended):
7-12VDC Input Voltage (limits): 6-20VDC Buckled

Analog Port : solid connection to 6 Analog inputs with VCC/GND.
Digital IO port : 13 ports prepared to digital
modules or servos.
Analog IO Port:2.54 grid male pin header connections.
Buckled Communication Port : Selectable between I2C and UARt.
Size:7cm x 5,8 cm (2.76inch x 2.28inch)
Technische Details:

Merkmale
Produkttyp
Bord-Sensor
Gewicht und Abmessungen
Gewicht
28 g

Weitere Bilder