

# Dynatron 2U server active cooler model S5

**Artikelnummer** 999857935

**Gewicht** 1kg

**Länge** 1mm

**Breite** 1mm

**Höhe** 1mm



## Produktbeschreibung

Dynatron 2U server active cooler model S5

Produktbeschreibung:

CPU Support Intel CPU Socket FCLGA 4677 Screw  
Type #8-32 Installation Torque 8 in-lb Solution  
2U Server and Up Dimensions 118 x 82 x 67 mm Weight  
470 g Material 5 Heatpipes with Aluminum Fin Base  
and Aluminum Fin Stack Fan Dimension 60 x 60 x  
25 mm Speed At Duty Cycle 0~20%: 2300±  
200 RPM At Duty Cycle 50%: 5400± 10% RPM  
At Duty Cycle 100%: 11000±10% RPM Rated  
Voltage 12V Bearing Double Ball Power At Duty  
Cycle 0~20%: 0.84 W At Duty Cycle 50%: 2.76 W  
At Duty Cycle 100%: 18.0 W Air Flow At Duty Cycle  
0~20%: 11.91 CFM At Duty Cycle 50%: 28.38 CFM  
At Duty Cycle 100%: 58.31 CFM Noise Level At Duty  
Cycle 0~20%: 25.8 dBA At Duty Cycle 50%: 44.4  
dBA At Duty Cycle 100%: 59.8 dBA Air Pressure  
At Duty Cycle 0~20%: 1.48 mm-H2O At Duty Cycle  
50%: 7.54 mm-H2O At Duty Cycle 100%: 28.8 mm-H2O  
Lead Wire Pin Out Pin#1-Black(-) Pin#2- Yellow(+)  
Pin#3- Green(Tachometer/  
Signal Output) Pin#4- Blue (PWM) Thermal Grease  
Shin-Etsu 7762 or Equivalent Life –  
Continuous operating under normal temperature  
(40 °C or 104 °F) 70,000 Hours  
Technische Details:

Allgemeines

Typ

CPU-Kühler

Bauart

Kühler

Geräuschpegel (dB)

25,8 dB

Eingangsspannung

12 V

Luftmenge pro Stunde

11,91 cfm

Gewicht

470 g

Abmessungen / Gewicht

Abmessungen

118 x 82 x 67 mm

## Weitere Bilder

