Planet Faseroptik 850nm 1000Mbit/s SFP Netzwerk-Transceiver-Modul SFP-Port 1000BASE-SX mini-GBIC module 550m

Artikelnummer	992008017
Gewicht	1kg
Länge	1mm
Breite	1mm
Höhe	1mm

Produktbeschreibung

Planet Faseroptik 850nm 1000Mbit/s SFP Netzwerk-Transceiver-Modul SFP-Port 1000BASE-SX mini-GBIC module 550m

Produktbeschreibung:

Manufacturer Code : MGB-SX. Planet MGB-SX SFP (mini-GBIC) - 1 LC 1000Base-SX Network - For Optical Network Data Networking - Optical FiberMulti-mode - Gigabit Ethernet - 1000Base-SX - Hot-pluggable Hot-swappable.The MGB family consists of Small Form Factor Pluggable (SFP) transceiver modules that are specifically designed for high performance integrated duplex data link over single mode optical fiber. These transceiver modules are compliant with the SFP Multisource Agreement (MSA) and hot pluggable. These modules offer an easy way to be installed in SFP MSA compliant ports at any time without the interruption of the host equipment operation.The MGB family of SFP Mini-GBIC Gigabit Ethernet modules can be installed in PLANET Switch products with SFP mini-GBIC interface.
The deployment distance can be extended from 100 meters (TP) 550 meters (Multi-Mode LC) and up to 120 kilometers (Single-Mode LC).To meet the increasing demand of the Industrial Ethernet fiber solution Planet releases the MGB-T series 1000BASE-SX/LX/BX transceivers that can operate reliably in electrically harsh climatically demanding and wide temperature range (-40? to 75?) environment.
The MGB-T series 1000BASE-SX/LX/BX transceivers provide easy and fast 1000BASE-SX/LX/BX connection for Planet wide temperature industrial equipment.
Technische Details:

Allgemein
Gerätetyp

SFP (Mini-GBIC)-Transceiver-Modul
Formfaktor
Plug-in-Modul
Netzwerk
Anschlusstechnik
Kabelgebunden
Verdrahtungstyp
1000Base-SX
Data Link Protocol
GigE
Datenübertragungsrate
1 Gbps
Optische Wellenlänge
850 nm
Maximaler Übertragungsbereich
550 m
Produktzertifizierungen
IEEE 802.3z
Erweiterung/Konnektivität
Schnittstellen
1 x Ethernet 1000Base-SX - LC multi-mode
Kompatible Steckplätze
1 x SFP (mini-GBIC)
Umgebungsbedingungen
Min Betriebstemperatur
0 °C
Max. Betriebstemperatur
50 °C

Produkteigenschaften

Netzwerk - Datenübertragungsrate	1 Gbps
Kompatible Steckplätze	1 x SFP (mini-GBIC)
Netzwerk - Typ	SFP (Mini-GBIC)-Transceiver-Modul
Bereitgestellte Schnittstelle - Schnittstellen	1 x Ethernet 1000Base-SX - LC multi-mode
Produkttyp	SFP (Mini-GBIC)-Transceiver-Modul
Netzwerk - Formfaktor	Plug-in-Modul
Netzwerk - Anschlusstechnik	Kabelgebunden

Weitere Bilder